

ELKE 4226

PROJECT PROJÉT

SPEC TYPE

NOTES



FELT FINISH FINI FEUTRE



ADDITIONAL PREMIUM COLORS AVAILABLE – SEE ACOUSTIC MATERIAL COLOR OPTIONS PAGE

COLOR MIX MIX COULEUR





FAMILY FAMILLE



4226U-27

4230



ORDERING SPECIFICATION		SPÉCIFICATION DE COMMANDE		CODE	
MODEL		MODÈLE			
4226-18		SMALL ELKE			
4226-27		MEDIUM ELKE			
4226-37		LARGE ELKE			
LIGHT SOURCE		SOURCE LUMINEUSE		LED	
(WATTAGE, LAMP TYPE, OTHER INFO)					
LED		REGULAR OUTPUT			
COLOR TEMPERATURE		TEMPÉRATURE DE COULEUR ^(A)			
27		2700K			
30		3000K			
35		3500K			
40*		4000K			
* LONGER LEAD TIME MAY APPLY, PLEASE CONTACT YOUR EUREKA REPRESENTATIVE					
COLOR RENDERING INDEX (CRI)		INDICE DE RENDU DE COULEUR (IRC)		90	
90		90+ CRI			
VOLTAGE		VOLTAGE			
120V		120 VOLT			
277V		277 VOLT			
CONTROL OPTION		OPTION DE CONTRÔLE			
DV		0-10V DIMMING (120V-277V)			
DP		PHASE DIMMING (120V ONLY)			
NLTAIR2*		NLIGHT AIR CONTROL GEN 2			
NLIGHT*		NLIGHT WIRED CONTROL			
* REQUIRES RC3 CANOPY					
* FOR EMERGENCY BATTERY WITH NLIGHT OPTIONS, PLEASE CONTACT YOUR EUREKA REPRESENTATIVE.					
REFER TO NLIGHT GUIDE AND INSTALLATION SHEET FOR ALL REQUIREMENTS.					
EMERGENCY BATTERY		BATTERIE D'URGENCE			
EM DRIVER BOX INCLUDED , INSTALLED REMOTELY. SEE EM GUIDE FOR DETAILS.					
EMB ⁽¹⁾		EMERGENCY BATTERY FOR REMOTE BOX			
⁽¹⁾ 3981E ACCESSORY IS REQUIRED FOR THIS OPTION					
CABLE		CÂBLE		C	
C		CLEAR CABLE, FIELD ADJUSTABLE			
CABLE LENGTH		LONGUEUR DE CÂBLE			
60		60" CABLE (STD LENGTH)			
**		CUSTOM CABLE LENGTH (PLEASE SPECIFY)			
FOR OVERALL LENGTH, PLEASE CONTACT YOUR EUREKA REPRESENTATIVE					
MOUNTING		MONTAGE			
		ROUND CANOPY / PAVILLON ROND			
RC1		SCREWLESS 1.35" CANOPY (2473F)			
RC2*		SCREWLESS 0.5" CANOPY (2471C)			
RC3		NLIGHT SCREWLESS CANOPY 07.75" x 1.30" (2474H)			
* 3983 ACCESSORY PROVIDED					
CANOPY FINISH		FINI PAVILLON			
BLKE		BLKE FINE TEXTURE			
WHE		WHITE FINE TEXTURE			
RAL*		PLEASE SPECIFY RAL CODE			
* LONGER LEAD TIME MAY APPLY, PLEASE CONTACT YOUR EUREKA REPRESENTATIVE					
POWER CORD FINISH		FINI CÂBLE D'ALIMENTATION		CLR	
CLR		CLEAR VINYL CABLE			
MAIN PANELS FELT FINISH		PANNEAUX PRINCIPAUX FINI FEUTRE			
ABF		AZURE BLUE FELT		BYF	BANANA YELLOW FELT
AWF		ARCTIC WHITE FELT		CHF	CHARCOAL FELT
BBF		BASIC BLACK FELT		NBF	NAVY BLUE FELT
BOF		BLOOD ORANGE FELT		OBF	OCEAN BLUE FELT
BTF		BATTLESHIP GRAY FELT		PGF	PEAR GREEN FELT
PREMIUM*		PLEASE SPECIFY PREMIUM COLOR CODE – SEE ACOUSTIC MATERIAL COLOR OPTIONS PAGE			
* LONGER LEAD TIME MAY APPLY, PLEASE CONTACT YOUR EUREKA REPRESENTATIVE					
BLADES FELT FINISH		AILES FINI FEUTRE			
ABF		AZURE BLUE FELT		BYF	BANANA YELLOW FELT
AWF		ARCTIC WHITE FELT		CHF	CHARCOAL FELT
BBF		BASIC BLACK FELT		NBF	NAVY BLUE FELT
BOF		BLOOD ORANGE FELT		OBF	OCEAN BLUE FELT
BTF		BATTLESHIP GRAY FELT		PGF	PEAR GREEN FELT
PREMIUM*		PLEASE SPECIFY PREMIUM COLOR CODE – SEE ACOUSTIC MATERIAL COLOR OPTIONS PAGE			
* LONGER LEAD TIME MAY APPLY, PLEASE CONTACT YOUR EUREKA REPRESENTATIVE					
ACCESSORY		ACCESSOIRE			
ALL ACCESSORIES ARE AVAILABLE FOR ADVANCE SHIPPING					
3983		DEEP JUNCTION BOX (PROVIDED)			
EMERGENCY BATTERY ACCESSORY		ACCESSOIRE BATTERIE D'URGENCE			
3981EA		ELECTRICAL BOX FOR EMB EMERGENCY BATTERY			


PRODUCT CHARACTERISTICS CARACTÉRISTIQUES DU PRODUIT




SPECIFICATION

Acoustic Material Color Options for Elke


Standard colors




ABF
Azure Blue




AWF
Arctic White



BBF
Basic Black



BOF
Blood Orange




BTF
Battleship Gray




BYF
Banana Yellow




CHF
Charcoal




NBF
Navy Blue



OBF
Ocean Blue



PGF
Pear Green




REF
Red



SGF
Silver Gray



TGF
Titanium Gray



ZFF
Zinfandel


Premium colors




BGF
Bubble Gum




BKF
Bark Brown



DBF
Denim Blue




DTF
Deep Teal Green



DYF
Daisy Yellow




GGF
Grass Green




LBF
Light Beige



LGF
Lime Green




MGF
Moss Green




OAF
Oak Brown



PBF
Peanut Brown



PNF
Pinot Noir



PPF
Plum Purple



SBF
Sky Blue



TOF
Tangerine Orange



TPF
Tulip Purple

- Premium colors carry extended lead times. Additional fees may apply for expedited lead times. Please consult factory.
- Due to the dye process, colors may vary slightly from batch to batch.

ELKE 4226

SEAMLESS INSTALLATION

Elke is suspended on a aircraft cable and powered with a clear power cable and is available with a standard 1,35in or a slim 0,5in magnetic canopy. Elke unlit is hung on an aircraft cable without canopy. 4226-18 is hung with power cable exclusively

MAIN PANELS

The main panels fulfill a strong geometric aspect

BLADES

The cut-open blades finish the bold look and keeps everything breathy. Blades can be a different felt color from the main panels. Unlit version has full blades.

BRACKETS

The brackets holds the blades in place and will always be the same color as the main panels

CLEANING

A proper and regular cleaning will help extend the lifespan of acoustic products. Remove dust with a vacuum cleaner and light stains with a damp cloth. For greasy and deep stains, a professional dry clean is recommended. Do no use any abrasive, soap, or chemical cleaner.



NOISE REDUCTION FIXTURES

Lighted versions (Elke 4226) or the versions without light source (Elke Unlit 4226U) can be used alone or combined to create impressive layouts, while multiplying the sound absorption.

BIG FAMILY

Elke is available in 3 sizes, allowing a lot of configurations. Also available as an unlit pendant (Elke Unlit 4226U)

SOUND ABSORBING SHADE

The shade is composed of interlocked sound absorbing panels that increases acoustic comfort.

ECOLOGICAL

Custom CNC cut polyester felt panels made from recycled bottles (PET). Panels are also recyclable.




MIXED FELT COLOR POSSIBILITY

It is possible to create a combination of 2 felt colors from our selection of Standard and Premium felt colors

COLORS

Available in 14 standard colors and 16 Premium colors, For all color options, refer to the Acoustic Material Color Options page.




PRODUCT SPECIFICATION	4226-18	4226-27	4226-37	4226U-18	4226U-27	4226U-37
PERFORMANCE						
SYSTEM WATTAGE	9.8 W	9.8 W	14.1 W	N/A	N/A	N/A
DELIVERED LUMENS (4000K)	677 LM	732 LM	1043 LM			
EFFICACY	70.5 LM/W	74.7 LM/W	73.1 LM/W			
OTHER INFORMATION						
WEIGHT	2.82 LBS / 1.28KG	6.28 LBS / 2.85 KG	11.46 LBS / 5.20 KG	1.76 LBS / 0.8KG	4.52 LBS / 2.05 KG	7.19 BS / 3.26 KG
L70 (LUMEN MAINTENANCE)	> 55 000 HRS	> 55 000 HRS	> 55 000 HRS	N/A	N/A	N/A
FELT	HIGH DENSITY 9MM POLYESTER FELT					
ACOUSTIC	ACOUSTIC MATERIAL RATED AT 0.75 N					
FIRE RATING	ASTM E84-13 (FELT MATERIAL ONLY)					
MAX. LUMINANCE 45°-90° OF NADIR	429 CD/M2	203 CD/M2	152 CD/M2	N/A	N/A	N/A

EFFICACY MULTIPLIERS

CRI	CCT	FACTOR
90+	4000K	1.00
90+	3500K	0.97
90+	3000K	0.94
90+	2700K	0.91

LIGHT DISTRIBUTION



4226-XX



Visit our website for warranty terms and conditions.

INSTALLATION SANS QUINCAILLERIE VISIBLE

Elke est suspendu sur câble d'acier ainsi qu'un câble électrique clair sur un pavillon magnétique standard de 1,35po ou mince de 0,5po. Elke Unlit est suspendu par câble d'acier sans pavillon. 4226-18 est suspendu par câble électrique seulement.

PANNEAUX PRINCIPAUX

Les panneaux principaux renforcent la géométrie.

AILETTES


Les ailes ajouré viennent alléger et permettre au look de respirer. Les ailettes peuvent être d'une couleur différente des panneaux principaux. La version sans source lumineuse à des ailettes pleines.

BRACKETS

Les brackets tiennent les ailettes en place et sont de la couleur des panneaux principaux

NETTOYAGE

Un nettoyage approprié et régulier contribuera à prolonger la durée de vie des produits acoustiques. Enlever la poussière avec un aspirateur et les taches légères avec un linge humide. Pour les tâches importantes ou graisseuses, un nettoyage à sec est recommandé. Ne pas utiliser de produits abrasifs, de savon ou de produits nettoyants chimiques.



FAMILLE DE PRODUIT

Elke est disponible en 3 formats, permettant un lot de configurations. Également disponible en suspension non éclairé (Elke Unlit 4226U)

ABAT-JOUR INSONORISANT

L'abat-jour du luminaire est composé de panneaux insonorisant entrecroisés qui augmentent le confort acoustique.

ÉCOLOGIQUE

Panneaux de polyester faits de bouteilles de plastique recyclées (PET) et coupés sur mesure. Les panneaux sont recyclables.



MIX DE COULEURS POSSIBLES


Il est possible de créer des combinaisons de 2 couleurs à travers notre sélection de feutres couleurs Standard ainsi que nos couleurs Premium

COULEURS

Disponible en 14 couleurs standards et 16 couleurs Premium. Pour toute les options, consultez la Fiche de Spécification

ATTÉNUATION DU BRUIT

Les versions éclairées (Elke 4226) ou sans source lumineuse (Elke Unlit 4226U) peuvent s'utiliser seules ou être disposés de façon à créer d'impressionnant agencement, multipliant ainsi l'absorption du bruit ambiant.




SPÉCIFICATION PRODUIT	4226-18	4226-27	4226-37	4226U-18	4226U-27	4226U-37
PERFORMANCE						
PUissance Totale	9.8 W	9.8 W	14.1 W	N/A	N/A	N/A
LUMENS RÉELS(4000K)	677 LM	732 LM	1043 LM			
EFFICACITÉ	70.5 LM/W	74.7 LM/W	73.1 LM/W			
AUTRES INFORMATIONS						
POIDS	2.82 LBS / 1.28 KG	6.28 LBS / 2.85 KG	11.46 LBS / 5.20 KG	1.76 LBS / 0.8KG	4.52 LBS / 2.05 KG	7.19 BS / 3.26 KG
L70 (MAINTENANCE DE LA LUMIÈRE)	> 55 000 H	> 55 000 H	> 55 000 H	N/A	N/A	N/A
FEUTRE	FEUTRE DE POLYESTER HAUTE DENSITÉ 9MM					
ACOUSTIQUE	MATÉRIEL ACOUSTIQUE GRADÉ À 0.75 N					
RÉSISTANCE AU FEU	ASTM E84-13 (MATÉRIEL FEUTRE SEULEMENT)					
MAX. LUMINANCE 45°-90° OF NADIR	429 CD/M2	203 CD/M2	152 CD/M2	N/A	N/A	N/A

FACTEUR D'EFFICACITÉ

CRI	CCT	FACTOR
90+	4000K	1.00
90+	3500K	0.97
90+	3000K	0.94
90+	2700K	0.91

DISTRIBUTION LUMINEUSE



4226-XX



